

EASY APPLY & REPOSITIONABLE SELF ADHESIVE OPAQUE FABRIC

COMPATIBLE WITH SOLVENT, ECO-SOLVENT, LATEX & UV INKS

Product description

- Easy to apply repositionable opaque self adhesive fabric - no need for messy glues or pastes
- Non reflective polyester, perfect for non-porous smooth flat or curved surfaces
- No residue when removed
- Dimensionally stable with no stretch or shrink
- Tear resistant & wrinkle free
- PVC and Phthalate free



FIRE RATED
EN 13501-1 certified

Specifications

| | | | |
|---------|--------|---------------|----------------|
| Length | 30m | Inner Core | 3" |
| Weight | 250gsm | Surface | Matte |
| Caliper | 295µm | Base Material | 100% Polyester |

Certified to the European standard C-s2, d0 fire rating in accordance with the testing procedures given in EN 13501-1: 2018 and EN 15102: 2007+A1: 2011.

Uses



Wall coverings, events, exhibitions, point of sale, interior design, advertising & promotions and commercial branding

Printing and handling

- Recommended conditions for use: 10~30°C / 30~65% RH
- To optimize the printing quality, printer needs to be set for highest print quality
- One year storage in original package at recommended temperature

Application tips

- Test the surface before use, samples are available, please contact us for details
- Clean and remove any loose material from the surface
- Ensure that painted surfaces are fully dry, it is recommended that vinyl paints are left for 3–4 weeks to gas off
- Always use a new blade when cutting
- Removal is recommended in cooler temperatures

**Important information: It is the responsibility of the purchaser to test and determine the suitability of the material. Printer and ink change may affect results. Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied.*

InkTec Europe

01993 862770 | info@inkteceu.com | www.inkteceu.com