SOFT TEXTURE ADHESION DIRECT TO FILM I

SUITABLE FOR PRINTING DIRECT TO FILM USING EPSON i3200 HEAD

Product description

- Direct to film printing ink with a soft printed finished image texture
- Superior printing quality and vivid colour performance, even with delicate graphics
- Excellent adhesion and transfer rate
- Superior soap and water resistance
- Maintains consistent quality under high speed with low production costs

Printer compatibility

Print Head	Туре
EPSON	Compatible with printers with Epson i3200 print head

Product codes and colours

Colour	1Kg Bottle
ВК	DTF-B01KC
С	DTF-B01KC
М	DTF-B01KM
Υ	DTF-B01KY
White	DTF-B01KW



The DTF process



Design

choice of design software (i.e. photoshop, illustrator, etc.



Create your design using your preferred If you are printing white on top of colour you will need to use a RIP.



Print

Print your design onto your choice of coated PET film.



Apply powder adhesive evenly onto printed film. If using manually, shake off excess or if using a powder shaker follow unit instructions.



Melt the adhesive onto the film using a heat press, oven or heated shaker unit. Ensure even heat through-out at a temperature of 160C.



Press your design onto a substrate. Applicable on cotton, polyester, leather, cardboard and other flat, rough and rigid materials.

