



# UV DTF PRINTER

## OVERALL FEATURES

- UV DTF Printer available in either a 30cm or 60cm width
- Printing and integrated automatic lamination
- Automatic ink supply, with varnish stirring and circulation
- In-built air cooling and back feed-in and front take up system
- Anti-collision system and laminated rubber roller

30CM UV DTF PRINTER SPECIFICATION	
Printer Model	30cm UV DTF Printer
Printhead	2pcs EPSON F1080
Printing Speed	4 Pass 3m <sup>2</sup> /hr   6 Pass 2.6m <sup>2</sup> /hr 8 Pass 2m <sup>2</sup> /hr   12 Pass 1.5m <sup>2</sup> /hr
Printing Width	300mm
Ink	CMYK+W+V
Print Media	UV DTF Film
RIP Software	Riin / Flexiprint / Cadlink / Maintop
Image Format	BMP, JPG, TIFF, EPS and PDF
Computer System	Windows 10 and above
Power Supply	110V/220V, 50-60 HZ, 400W
Ideal Operating Environment	TEMP.: 20°C-30°C Humidity: 35%-65%
Dimensions	910 x 949 x 1078mm
Weight	116kg

60CM UV DTF PRINTER SPECIFICATION	
Printer Model	60cm UV DTF Printer
Printhead	3 pcs EPSON i3200
Printing Speed	4 Pass 5m <sup>2</sup> /hr   6 Pass 4m <sup>2</sup> /hr 8 Pass 3m <sup>2</sup> /hr
Printing Width	600mm
Ink	CMYK+W+V or G+W+CMYK+V
Print Media	UV DTF Film
RIP Software	Riin / Flexiprint / Cadlink / Maintop
Image Format	BMP, JPG, TIFF, EPS and PDF
Computer System	Windows 10 and above
Power Supply	110V/220V, 50-60 HZ, 1800W
Ideal Operating Environment	TEMP.: 20°C-30°C Humidity: 35%-65%
Dimensions	1800 x 870 x 1600mm
Weight	Approx. 200kg