SUPER SOFT FINISH DTF ADHESIVE POWDER

SUITABLE FOR USE AS PART OF THE DTF PROCESS

Product description

- DTF adhesive powder with a soft texture printed image finish
- Works well with both white and black garments and products
- Stretchable and durable even after washing to resist cracking
- Superior soap and water resistance
- Maintains consistent quality under high speed with low production costs

Printer compatibility

Print Head	Туре
EPSON	Compatible with printers with Epson i3200 print head

Product features

- Manufactured in the EU
- Granulation 80-220mic
- Melting range 95-110°c
- Pressing temperature 140 170°C
- Washable up to 60°C
- Extensively trialled and tested
- REACH AND ISO9001 compliant for quality control





The DTF process



Create your design using your preferred If you are printing white on top of colour choice of design software (i.e. photoshop, illustrator, etc.



you will need to use a RIP.



Print

Print your design onto your choice of coated PET film.



Apply powder adhesive evenly onto printed film. If using manually, shake off excess or if using a powder shaker follow unit instructions.



Melt the adhesive onto the film using a heat press, oven or heated shaker unit. Ensure even heat through-out at a temperature of 160C.



Press your design onto a substrate. Applicable on cotton, polyester, leather, cardboard and other flat, rough and rigid

